MARSHALL EXCELSIOR COMPANY

ME481 Last Chance Adapter User Instructions

WARNING: These products contain a chemical known to the state of California to cause cancer and birth defects or reproductive harm

1. Close valve on 20 lb. cylinder and remove from beneath grill before using.
   For POL Application Remove Internal Gasket on Last Chance Adapter Before Installation
2. Connect to appliance.
3. Connect adapter to disposable cylinder (Either 14.1 oz. tall or 16.4 oz. short)
4. Leak check connections at the disposable cylinder and at the appliance B connection using a mixture of water and non-ammonia soap.
5. The disposable cylinder should be used in the upright position to assure vapor feed.
   CAUTION: Do not use the adapter in the upside down position. This will result in feeding liquid propane into the gas train and result in a fire hazard.
6. Remove disposable cylinder from Last Chance Adapter and dispose of empty tank in proper waste receptacle before removing adapter from appliance hose.

CAUTION: Keep the tank and hose assembly from hot surfaces.

Instruction #414 Rev-C 2/21/18

MARSHALL EXCELSIOR COMPANY

ME481 Last Chance Adapter User Instructions

WARNING: These products contain a chemical known to the state of California to cause cancer and birth defects or reproductive harm

1. Close valve on 20 lb. cylinder and remove from beneath grill before using.
   For POL Application Remove Internal Gasket on Last Chance Adapter Before Installation
2. Connect to appliance.
3. Connect adapter to disposable cylinder (Either 14.1 oz. tall or 16.4 oz. short)
4. Leak check connections at the disposable cylinder and at the appliance connection using a mixture of water and non-ammonia soap.
5. The disposable cylinder should be used in the upright position to assure vapor feed.
   CAUTION: Do not use the adapter in the upside down position. This will result in feeding liquid propane into the gas train and result in a fire hazard.
6. Remove disposable cylinder from Last Chance Adapter and dispose of empty tank in proper waste receptacle before removing adapter from appliance hose.

CAUTION: Keep the tank and hose assembly from hot surfaces.

Instruction #414 Rev-C 2/21/18

MARSHALL EXCELSIOR COMPANY

ME481 Last Chance Adapter User Instructions

WARNING: These products contain a chemical known to the state of California to cause cancer and birth defects or reproductive harm

1. Close valve on 20 lb. cylinder and remove from beneath grill before using.
   For POL Application Remove Internal Gasket on Last Chance Adapter Before Installation
2. Connect to appliance.
3. Connect adapter to disposable cylinder (Either 14.1 oz. tall or 16.4 oz. short)
4. Leak check connections at the disposable cylinder and at the appliance connection using a mixture of water and non-ammonia soap.
5. The disposable cylinder should be used in the upright position to assure vapor feed.
   CAUTION: Do not use the adapter in the upside down position. This will result in feeding liquid propane into the gas train and result in a fire hazard.
6. Remove disposable cylinder from Last Chance Adapter and dispose of empty tank in proper waste receptacle before removing adapter from appliance hose.

CAUTION: Keep the tank and hose assembly from hot surfaces.

Instruction #414 Rev-C 2/21/18

MARSHALL EXCELSIOR COMPANY

ME481 Last Chance Adapter User Instructions

WARNING: These products contain a chemical known to the state of California to cause cancer and birth defects or reproductive harm

1. Close valve on 20 lb. cylinder and remove from beneath grill before using.
   For POL Application Remove Internal Gasket on Last Chance Adapter Before Installation
2. Connect to appliance.
3. Connect adapter to disposable cylinder (Either 14.1 oz. tall or 16.4 oz. short)
4. Leak check connections at the disposable cylinder and at the appliance connection using a mixture of water and non-ammonia soap.
5. The disposable cylinder should be used in the upright position to assure vapor feed.
   CAUTION: Do not use the adapter in the upside down position. This will result in feeding liquid propane into the gas train and result in a fire hazard.
6. Remove disposable cylinder from Last Chance Adapter and dispose of empty tank in proper waste receptacle before removing adapter from appliance hose.

CAUTION: Keep the tank and hose assembly from hot surfaces.

Instruction #414 Rev-C 2/21/18

MARSHALL EXCELSIOR COMPANY

ME481 Last Chance Adapter User Instructions

WARNING: These products contain a chemical known to the state of California to cause cancer and birth defects or reproductive harm

1. Close valve on 20 lb. cylinder and remove from beneath grill before using.
   For POL Application Remove Internal Gasket on Last Chance Adapter Before Installation
2. Connect to appliance.
3. Connect adapter to disposable cylinder (Either 14.1 oz. tall or 16.4 oz. short)
4. Leak check connections at the disposable cylinder and at the appliance connection using a mixture of water and non-ammonia soap.
5. The disposable cylinder should be used in the upright position to assure vapor feed.
   CAUTION: Do not use the adapter in the upside down position. This will result in feeding liquid propane into the gas train and result in a fire hazard.
6. Remove disposable cylinder from Last Chance Adapter and dispose of empty tank in proper waste receptacle before removing adapter from appliance hose.

CAUTION: Keep the tank and hose assembly from hot surfaces.

Instruction #414 Rev-C 2/21/18

MARSHALL EXCELSIOR COMPANY

ME481 Last Chance Adapter User Instructions

WARNING: These products contain a chemical known to the state of California to cause cancer and birth defects or reproductive harm

1. Close valve on 20 lb. cylinder and remove from beneath grill before using.
   For POL Application Remove Internal Gasket on Last Chance Adapter Before Installation
2. Connect to appliance.
3. Connect adapter to disposable cylinder (Either 14.1 oz. tall or 16.4 oz. short)
4. Leak check connections at the disposable cylinder and at the appliance connection using a mixture of water and non-ammonia soap.
5. The disposable cylinder should be used in the upright position to assure vapor feed.
   CAUTION: Do not use the adapter in the upside down position. This will result in feeding liquid propane into the gas train and result in a fire hazard.
6. Remove disposable cylinder from Last Chance Adapter and dispose of empty tank in proper waste receptacle before removing adapter from appliance hose.

CAUTION: Keep the tank and hose assembly from hot surfaces.

Instruction #414 Rev-C 2/21/18

MARSHALL EXCELSIOR COMPANY

ME481 Last Chance Adapter User Instructions

WARNING: These products contain a chemical known to the state of California to cause cancer and birth defects or reproductive harm

1. Close valve on 20 lb. cylinder and remove from beneath grill before using.
   For POL Application Remove Internal Gasket on Last Chance Adapter Before Installation
2. Connect to appliance.
3. Connect adapter to disposable cylinder (Either 14.1 oz. tall or 16.4 oz. short)
4. Leak check connections at the disposable cylinder and at the appliance connection using a mixture of water and non-ammonia soap.
5. The disposable cylinder should be used in the upright position to assure vapor feed.
   CAUTION: Do not use the adapter in the upside down position. This will result in feeding liquid propane into the gas train and result in a fire hazard.
6. Remove disposable cylinder from Last Chance Adapter and dispose of empty tank in proper waste receptacle before removing adapter from appliance hose.

CAUTION: Keep the tank and hose assembly from hot surfaces.

Instruction #414 Rev-C 2/21/18