



ME868BLK BYPASS LINE KIT

Installation Instructions



WARNING

- Failure to follow these instructions or to properly install and maintain this equipment could result in (A) personal injury or death and (B) an explosion and/or fire causing property damage.
- Install, operate and maintain Marshall Excelsior Co. equipment in accordance with federal, state, and local codes and these instructions. The installation in most states must also comply with NFPA #58 LP-Gas Code, ANSI K61.1 and DOT standards.
- Only personnel trained in the proper procedures codes, standards and regulations of the LP-Gas Industry should install and service this equipment.

CAUTION: Contact or inhalation of liquid propane or propane vapors can cause serious injury or death! Disperse propane only in accordance with local regulations. To prevent exposure of LP-Gas to people and livestock when allowed by regulations, release these chemicals outdoors in air currents that will ensure dispersion. Keep LP-gas far enough from any open flame or other source of ignition to prevent fire or explosion! LP-Gas is heavier than air and may not disperse or evaporate quickly if released in still air.

FOR USE WITH:

This product is compatible with ME825-16 2" High Flow Globe Valve when installed in combination with P/N ME868 Series Turbo-Flo LE Low Emission ACME Adapter.

WARNING

Release all system pressure prior to installation of bypass line kit. Failure to do so could result in personal injury. Use proper safety equipment at all times.

If ME868 series Turbo-Flo LE Low Emission Adapter is already installed, trapped liquid must be purged prior to bringing vehicle indoors for service or installation of bypass line kit. To purge, use adapter P/N MEP105 and follow instructions provided.



WARNING: These products contain a chemical known to the state of California to cause cancer and birth defects or reproductive harm

Marshall Excelsior Co.

1506 George Brown Drive Marshall, MI 49068

Phone (269) 789-6700 Fax (269) 781-8340

The contents of this publication are for informational purposes only. While every effort has been made to ensure accuracy, these contents are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or for their use or applicability. Marshall Excelsior Co. reserves the right to modify or improve the designs or specifications of such products at any time without notice. The MEC™ logo is the trademark of Marshall Excelsior.

Form # 444 Rev. C



ME868BLK BYPASS LINE KIT

Installation Instructions



WARNING

- Failure to follow these instructions or to properly install and maintain this equipment could result in (A) personal injury or death and (B) an explosion and/or fire causing property damage.
- Install, operate and maintain Marshall Excelsior Co. equipment in accordance with federal, state, and local codes and these instructions. The installation in most states must also comply with NFPA #58 LP-Gas Code, ANSI K61.1 and DOT standards.
- Only personnel trained in the proper procedures codes, standards and regulations of the LP-Gas Industry should install and service this equipment.

CAUTION: Contact or inhalation of liquid propane or propane vapors can cause serious injury or death! Disperse propane only in accordance with local regulations. To prevent exposure of LP-Gas to people and livestock when allowed by regulations, release these chemicals outdoors in air currents that will ensure dispersion. Keep LP-gas far enough from any open flame or other source of ignition to prevent fire or explosion! LP-Gas is heavier than air and may not disperse or evaporate quickly if released in still air.

FOR USE WITH:

This product is compatible with ME825-16 2" High Flow Globe Valve when installed in combination with P/N ME868 Series Turbo-Flo LE Low Emission ACME Adapter.

WARNING

Release all system pressure prior to installation of bypass line kit. Failure to do so could result in personal injury. Use proper safety equipment at all times.

If ME868 series Turbo-Flo LE Low Emission Adapter is already installed, trapped liquid must be purged prior to bringing vehicle indoors for service or installation of bypass line kit. To purge, use adapter P/N MEP105 and follow instructions provided.



WARNING: These products contain a chemical known to the state of California to cause cancer and birth defects or reproductive harm

Marshall Excelsior Co.

1506 George Brown Drive Marshall, MI 49068

Phone (269) 789-6700 Fax (269) 781-8340

The contents of this publication are for informational purposes only. While every effort has been made to ensure accuracy, these contents are not to be construed as warranties or guarantees, expressed or implied, regarding the products or services described herein or for their use or applicability. Marshall Excelsior Co. reserves the right to modify or improve the designs or specifications of such products at any time without notice. The MEC™ logo is the trademark of Marshall Excelsior.

Form # 444 Rev. C