





ME480 Full Flow


APPLICATION:

Designed to provide a quick way to change from a 20 pound cylinder to a 1 pound disposable cylinder. Can be used to connect a small 1 pound disposable cylinder to a gas grill or other appliance.

NOTE: To use the female POL on the ME480 series, simply remove the internal gasket. The gasket must be in place to use the Type I (QCC) connection (reference pg. 183).

| Part No. | Inlet | Outlet | Description |
|------------|--------------|--------|---------------------|
| ME480 | 1"-20 Female | M. POL | Full Flow |
| ME480EX | 1"-20 Female | F. QCC | 0.9 GPM Excess Flow |
| ME480EX1.8 | 1"-20 Female | F. QCC | 1.8 GPM Excess Flow |
| ME481 | 1"-20 Female | F. QCC | Shutoff Poppet |

^{*} An excess flow device does not provide a 100% shutoff, a small amount of propane may leak if disconnected.



CAUTION: The disposable cylinder must always be within 45 degrees of the upright (vertical) position when connected to the grill connection. Failure to do so can result in LP in its liquid form entering the grill. This could result in explosion, fire hazard or personal injury.

WARNING: Keep disposable cylinder and grill connection away from open flames, or hot surfaces. Failure to do so can result in explosion, fire hazard or personal injury



