Mini Quad-Port Relief Valve Manifold

APPLICATION:

For use with large LPG & NH₃ stationary storage containers with 2" FNPT openings. These Relief Manifolds have an additional relief valve excluded from the flow rating, which allows for service and/or exchange of any one relief valve without evacuating the tank. Our large port selection handle allows for each specific valve port to be closed off so that the relief valve may be removed while the remaining valves stay under pressure protecting the tank and contents. Each manifold model is rated based on the flow through the relief valves with one valve removed from service.

COVERS MOST
30,000 GALLON TANKS
WITH
ONLY TWO MANIFOLDS

ME904S-16/250



FEATURES:

- · Heavy Duty Ductile Iron Body
- · All Stainless Steel Internal Components
- · Durable Teflon V-Pack Stem Seals
- · Large Diameter Port Selection Handle and Port Indicator
- · Molded Rubber Weather Guard for Manifold Rotary Gear with Port Plug
- · Available with 250 PSIG and 265 PSIG Relief Valve Set Pressures
- · Vapor Equalizing Feature for Easy Port to Port Rotation
- · Includes Tank Stabilizer Nut for Maximum Strength at Container Connection



MEP178K (Pipeaway Adapter & Stabilizer Kit)



	Relief Valve	Application		Tank Connection	Reli	ief Valve	***Flow Rating SCFM/AIR @ 120% of set pressure
Part No.	STD	LPG	NH ₃	Size	# of Valves	Part No.	UL Rating
ME902S-16B/250	250 PSIG	YES	NO	2" MNPT	2	MEV125B/250	5,115 (1)
ME902S-16/250	250 PSIG	NO	YES	2" MNPT	2	MEV125/250	5,115 (1)
ME902S-16/265	265 PSIG	NO	YES	2" MNPT	2	MEV125/265	5,855 (1)
ME903S-16B/250	250 PSIG	YES	NO	2" MNPT	3	MEV125B/250	9,320 (2)
ME903S-16/250	250 PSIG	NO	YES	2" MNPT	3 MEV125/250		9,320 (2)
ME903S-16/265	265 PSIG	NO	YES	2" MNPT	3	MEV125/265	10,795 (2)
ME904S-16B/250	250 PSIG	YES	NO	2" MNPT	4	MEV125B/250	12,481 (3)
ME904S-16/250	250 PSIG	NO	YES	2" MNPT	4	MEV125/250	12,481 (3)
ME904S-16/265	265 PSIG	NO	YES	2" MNPT	4	MEV125/265	13,630 (3)

^{***}Flow rating based on number of valves indicated in parenthesis ().

Flow rates shown are for bare relief valves, pipaways will reduce flow rates.

Note: For 265 PSIG set pressure change part number suffix - i.e. ME903S-16/265

To order FKM seal materials add "VM" after the prefix part number - i.e. ME904S-16B/250VM

Accessories						
Part No.	Description					
MEV125-109	Replacement Plastic Rain Cap for MEV125 Series Relief Valves - Black					
MEP178	Pipeaway Adapter for MEV125 Series w/ 2" FNPT Outlet - Aluminum					
MEP178K	Pipeaway Adapter Kit w Stabilizer Bracket for ME904S-16					
MEP123	Installation / Removal Tool for MEV125 Series Relief Valves					

SEE BACK FOR TANK SIZING CHART





TANK SIZING REFERENCE CHART											
			LPG		NH3						
Part No.	Relief Valve STD	30,000 Gallon 109" O.D.	30,000 Gallon 131" O.D.	18,000 Gallon 109" O.D.	30,000 Gallon 109" O.D.	30,000 Gallon 131" O.D.	18,000 Gallon 109" O.D.				
ME902 Series	250 PSIG	N/A	5	3	2	2	2				
ME902 Series	265 PSIG	N/A	N/A	3	2	2	2				
ME903 Series	250 PSIG	3	3	2	2	1	1				
ME903 Series	265 PSIG	3	3	2	2	1	1				
ME904 Series	250 PSIG	3	2	2	1	1	1				
ME904 Series	265 PSIG	3	2	2	1	1	1				

^{*} Number indicates quantity of relief manifolds to adequated relief vapor overpressure conditions for listed tank surface areas



