

Mini Quad-Port Manifold

APPLICATION:

For use with large LPG & NH₃ stationary storage containers with 2" FNPT openings. These Relief Manifolds can accept up to 4 relief valves depending on the required SCFM relief capacity needed for a specific tank. One relief valve port can be closed off, which allows for service and/or exchange of any one relief valve without evacuating the tank. Our large port selection handle allows for each specific valve port to be closed off so that the relief valve may be removed while the remaining valves stay under pressure protecting the tank and contents.

FEATURES:

- Heavy duty ductile iron body
- All stainless steel internal components
- Durable PTFE V-pack stem seals
- Large diameter port selection handle and port indicator
- Molded rubber weather guard for manifold rotary gear with port plug
- Vapor equalizing feature for easy port-to-port rotation
- Includes tank stabilizer nut for maximum strength at container connection

ME904S-16



Part No.	Application		Tank Connection Size	Relief Valve Port	
	LPG	NH ₃		# of Valves	
ME904S-16	Yes	Yes	2" MNPT	1-1/4" FNPT (4)	
Accessories					
Part No.	Description	Application			
		LPG	NH ₃		
MEV125/250	1-1/4"MNPT External Relief Valve-Nitrile 250PSI - 6,328 SCFM	No	Yes		
MEV125/265	1-1/4"MNPT External Relief Valve-Nitrile 265PSI - 6,542 SCFM	No	Yes		
MEV125B/250	1-1/4"MNPT External Relief Valve-Nitrile 250PSI - 6,328 SCFM	Yes	No		
MEV125B/265	1-1/4"MNPT External Relief Valve-Nitrile 265PSI - 6,542 SCFM	Yes	No		

