

FULL SIZE SECOND STAGE DOMESTIC REGULATORS

PATENT PENDING



MEGR-1622
Full Size Series

PATENT PENDING



MEGR-1652
Full Size Back Mount Series

APPLICATION:

These **Excelsa-Flo™** second stage regulators are used to reduce outlet pressures from first stage regulators (normally 10 PSI) to 11" WC in domestic installations. All MEC second stage regulators are green indicating low outlet pressure. Second stage full size regulator vents have 3/4" FNPT tapped ports and our exclusive **E-Zgrip** screens located over the inlet. All MEC second stage domestic regulators feature a stainless steel inlet filter screen to reduce debris from passing through the regulator. Both the MEGR-1622 and the MEGR-1652 Series offer optimal relief performance that exceeds UL test requirements providing double failure overpressure protection (no more than 2 PSI downstream pressure) when used with MEGR-1122H and MEGR-1622H Series First Stage regulators. All MEC **Excelsa-Flo™** domestic regulators feature a 25 year recommended replacement life and our exclusive tear away leak check adhesive sticker.

SPECIFICATIONS:

Type: Second Stage
Max. Inlet Pressure: 10 PSIG
Exterior Finish: Green Powder Coat
Interior Finish: Green Powder Coat
Orifice Size: 0.219
Diaphragm: Fabric Reinforced (NBR) Molded Lip O-Ring Bonnet/Body Seal
Relief Type: Internal Relief - Spring Loaded
Bonnet / Body Material: Die Cast Aluminum
Seat Material: Fluorocarbon (FKM)
Listings: cUL_{US} / UL 144
Mounting Holes: Standard 3-1/2" Center
Pressure Taps: #54 Orifice 1/8" FNPT Plugged (2)
Relief Travel Stop: Molded In Adjustment Cap: Black

MEGR-1622 & MEGR-1652 Series:

Offers all of the same features as the compact MEGR-1122 Series but in a full size, high capacity version. Our full size second stage regulators have a large fabric reinforced diaphragm for superior downstream regulation, heavy duty wrench flats, and a large 3/4" FNPT tapped drip lip vent to help prevent relief valve blockage. The MEGR-1622 Series have both the inlet and outlet in line where the MEGR-1652 series have a rear discharge back mount outlet for convenient wall mount applications.

Part No.	Type	Capacity in BTU/H LPG ⁽¹⁾	Inlet	Outlet	Outlet Adj. Range ("WC)	Outlet Set Point ("WC)
MEGR-1622-BCF	Full Size	710,000	1/2" FNPT	1/2" FNPT	9-13	11
MEGR-1622-CFF	Full Size	1,300,000	1/2" FNPT	3/4" FNPT	9-13	11
MEGR-1622-DFF	Full Size	1,300,000	3/4" FNPT	3/4" FNPT	9-13	11
MEGR-1622-DFFXO⁽³⁾	Full Size	1,300,000	3/4" FNPT	3/4" FNPT	9-13	11
MEGR-1652-CFF⁽²⁾	Back Mount	1,000,000	1/2" FNPT	3/4" FNPT	9-13	11
MEGR-1652-DFF⁽²⁾	Back Mount	1,000,000	3/4" FNPT	3/4" FNPT	9-13	11

(1) Based on 10 PSIG inlet pressure and 20% droop

(2) Indicates back mount configuration

(3) Indicates vent over outlet



For Your Local Marshall Excelsior Distributor Call 269-789-6700,
 Fax 269-781-8340 or E-mail: sales@marshallexcelsior.com
www.marshallexcelsior.com



Tested in the
U.S.A