## Excela-Flo Low Pressure Single Stage Regulators **MEGR-230 SERIES**

## DESCRIPTION

The MEGR-230 single-stage regulators are approved for use in small portable applications and outdoor cooking appliances ulitizing low pressure.

NOTE: SINGLE STAGE REGULATORS DO NOT MEET RVIA REQUIREMENTS FOR USE RECREATIONAL VEHICLES. A119.2/NFPA 501C

## SPECIFICATIONS

Type: Single Stage Orifice Diameter: 0.059 Dia BTU Capacity: 140,000 BTU (based on 25 PSI inlet @ 20% droop) Max. Inlet Pressure: 250 PSI Inlet Connection: 1/4" FNPT **Outlet Connection: 3/8" FNPT** Exterior Finish: Green Wet Coat Diaphragm: Molded with O-Ring Bonnet / Body Seal Diaphragm Type: Internal Relief - Spring Loaded Bonnet / Body Material: Die Cast Aluminum Listings: 🕕 LISTED / UL 144 Mounting Holes: 3-1/2" On Center



Regulator with Drip Lip Vent



MEGR-230-9 MEGR-230 with Soft-Nose Excess Flow POL

Part No.	Description
MEGR-218	Single Stage Regulator - SN FF POL w/ Plastic Handwheel x 3/8" FNPT - 90° Vent
MEGR-230	Single Stage Regulator - 1/4" FNPT Inlet X 3/8" FNPT Outlet
MEGR-230-9	Single Stage Regulator - SN .9 GPM Excess Flow POL Inlet x 3/8" FNPT Outlet
MEGR-230-90	Single Stage Regulator - 1/4" FNPT Inlet X 3/8" FNPT Outlet - 90° Vent
MEGR-230-1618	Single Stage Regulator - Black F. QCC x 3/8" FNPT - 90° Vent
MEGR-230-1326	Single Stage Regulator - Black Female QCC Inlet (100,000 BTU/ H) x 3/8" FNPT Outlet
MEGR-231	Single Stage Regulator - Hardnose FF POL x 3/8" FNPT - 90° Vent



For Your Local Marshall Excelsior Distributor Call 269-789-6700, Fax 269-781-8340 or E-mail: sales@marshallexcelsior.com www.marshallexcelsior.com

