## SECOND STAGE / INDUSTRIAL REGULATORS MEGR-1133 SERIES



## APPLICATION:

The MEGR-1133 Series Second Stage / Industrial regulators are large capacity, self operated, low or high pressure units for use in applications with loads up to 110,000,000 BTU/H capacity. These regulators are best suited for industrial applications where high flow capacity and a downstream monitor control line is required.

Part No.	Description	Inlet/Outlet	Orifice	Range of Adjustment	Outlet Set Point	BTU/H LPG @ 10 PSI Inlet	BTU/H LPG @ 20 PSI Inlet
MEGR-1133H-2	Second Stage Regulator	2" FNPT	2"	2-5 PSI	2 PSI	27,405,000	52,700,000
MEGR-1133H-3	Second Stage Regulator	2" FNPT	2"	5-10 PSI	5 PSI	22,300,000	41,600,000
MEGR-1133L-4	Second Stage Regulator	2" FNPT	2"	8.5"-18" WC	14" WC	45,600,000	77,100,000
MEGR-1133L-6	Second Stage Regulator	2" FNPT	2"	.75-2 PSI	2 PSI	46,700,000	77,100,000

MEGR-1133 SPECIFICATIONS:						
Туре:	Adjustable/PSI/WC					
Orifice Diameter:	2″					
Orifice Material:	Aluminum					
Max. Inlet Pressure:	60 PSI					
Regulator Spring:	Steel					
Stem Guide/Disk Holder:	Aluminum					
Valve Stem:	Aluminum					
Exterior Finish:	Gray Powder Coat					
Diaphragm:	Fabric Reinforced Nitrile (NBR)					
Body Material:	Iron					
Bonnet Cap & Bonnet:	Aluminum					

\* Other configurations and materials available upon request.





For Your Local Marshall Excelsior Distributor Call 269-789-6700, Fax 269-781-8340 or E-mail: sales@marshallexcelsior.com www.marshallexcelsior.com