

# HIGH PRESSURE LP GAS REGULATORS



inside view



cut-away view



**MEGR-130-20**  
Pre-set at 20 PSIG



inside view



cut-away view



**MEGR-350**  
Adjustable 0-10 PSIG

The MEGR-130 series fixed high pressure single stage regulators are designed to provide an economical solution for pounds to pounds service applications. The MEGR-130 can be used to regulate air as well as LP gas. Regulators must be installed in compliance with federal, state or local codes or laws in accordance with NFPA 58.

The MEGR-350 is a single stage, adjustable high pressure regulator. The body and bonnet of both the fixed and adjustable regulators are precisely machined and feature a crimped design and fabric reinforced rubber diaphragm creating a positive seal for leak-free performance.

The MEGR-360 with the Type I (QCC) is designed specifically for appliances such as turkey fryers, fish fryers, camp stoves and torch applications that require pounds to pounds pressure instead of inches water column. These regulators will meet or exceed most requirements on a specific outlet setting (0-10 PSI) depending on the application.

Part No.	Description
<b>MEGR-130-05</b>	Compact High Pressure Fixed Reg 5 PSI - 1/4" FNPT Inlet/Outlet
<b>MEGR-130-10</b>	Compact High Pressure Fixed Reg 10 PSI - 1/4" FNPT Inlet/Outlet
<b>MEGR-130-20</b>	Compact High Pressure Fixed Reg 20 PSI - 1/4" FNPT Inlet/Outlet
<b>MEGR-130-30</b>	Compact High Pressure Fixed Reg 30 PSI - 1/4" FNPT Inlet/Outlet
<b>MEGR-350</b>	Compact High Press. Adjustable Reg 0-10 PSI - 1/4" FNPT Inlet/Outlet
<b>MEGR-350-20</b>	Compact High Press. Adjustable Reg 0-20 PSI - 1/4" FNPT Inlet/Outlet
<b>MEGR-350-30</b>	Compact High Press. Adjustable Reg 0-30 PSI - 1/4" FNPT Inlet/Outlet
<b>MEGR-351</b>	Compact High Pressure Adjustable Reg 0-10 PSI - Full Flow POL x 1/4" FNPT
<b>MEGR-360</b>	Compact High Pressure Adjustable Reg 0-10 PSI - Black F. QCC x 1/4" FNPT

## Specifications:

Type:	Adjustable or Fixed / PSI
Max. Inlet Pressure:	250 PSIG (17,2 bar)
Inlet Connection:	1/4" FNPT
Outlet Connections:	1/4" FNPT
Orifice Diameter:	0.0625"
Exterior Finish:	Red Anodized
Diaphragm:	Fabric Reinforced Buna N
Body/ Bonnet Material:	Die Cast Zinc
BTU/H Capacity:	1,200,000 BTU/H @ 40 PSI
Listings:	UL LISTED / UL 144