

# Dual Shutoff Break-Away Valves

*FLOKILL*™

BY 




ME860S-6  
Bracket Style



ME861S-6  
Lanyard Style

**Application:** For use with vapor or liquid lines to protect against pull-aways during transfer operations including transports, delivery trucks, motor fuel containers and other miscellaneous filling operations.

## Features:

- For use with LP Gas and NH<sub>3</sub>
- Buna-N soft seat provides positive shutoff both upstream and downstream of source
- 100 - 300 lbs of force required for disconnect
- Approximately 100 lbs of force to reconnect
- Available with bracket or lanyard style
- Durable all steel construction
- Large internal bore for increased flow
- Meets all  requirements for hose end swivel and break-away devices

Break-Away Valves			
Part No.	Description	OAL	Style
ME860S-6	3/4" FNPT x 3/4" FNPT Break-Away	6"	Bracket
ME861S-6	3/4" FNPT x 3/4" FNPT Break-Away	6"	Lanyard
ME860S-8	1" FNPT x 1" FNPT Break-Away	6-3/4"	Bracket
ME861S-8	1" FNPT x 1" FNPT Break-Away	6-3/4"	Lanyard
ME860S-10	1-1/4" FNPT x 1-1/4" FNPT Break-Away	7-3/4"	Bracket
ME861S-10	1-1/4" FNPT x 1-1/4" FNPT Break-Away	7-3/4"	Lanyard
Accessories			
Part No.	Description		
MEP128-6	Re-assembly tool for 3/4" FNPT Breakaway		



NOTE: It is recommended that break-away valves be safety tested monthly to confirm that proper separation occurs in the event of a pull-away. An inert gas such as dry nitrogen is suggested for a source of pressure during testing.

**Marshall Excelsior**  
—  —  
**Gas Connections**

For Your Local Marshall Excelsior Distributor Call 269-789-6700,  
Fax 269-781-8340 or E-mail: [sales@marshallexcelsior.com](mailto:sales@marshallexcelsior.com)  
[www.marshallexcelsior.com](http://www.marshallexcelsior.com)

  
Made in the  
U.S.A.