

# High Flow MER425H & MER426H Series Pigtails

MER425H High Flow Series Hoses



MER426H High Flow Series Hoses



## Description

Specifically designed to meet the high demands of today's motorhomes, trailers and on demand hot water heaters.

Our new High Flow Type I 400,000 BTU (red nut) pigtails are designed for those applications that require more than 200,000 BTU's. The new High Flow pigtails are designed with both excess flow and thermal link safety features, same as the green nut Type I.

The RV Thermo Pigtail (Type I ACME) provides a safe, user-friendly connection from your Marshall Excelsior MEGR-253/253H regulator to a standard LP gas cylinder without the use of a wrench. The easy to tighten nylon nut swivels on a connector fitting that is heat sensitive. Between 240°F and 300°F the brass nipple displaces (approximately 1/4") closing the cylinder valve module and stopping the flow of gas from the container. Inside the brass nipple is a flow-limiting device designed to sense excess gas flow. If excessive gas flow is detected, the RV Thermo Pigtail will shut down the flow to a maximum of 10 SCFH (by-pass flow). This product is required by RVIA (Recreational Vehicle Industry Association) as original equipment on your RV and should be maintained to the highest standards. Because of this required standard, when opening or refilling your LP gas cylinders, it could take as long as 20 minutes to re-pressurize your LP gas system for normal appliance(s) operation.

NOTE: MEC green Type I Nut for use on RV application ONLY.  
(200,000 BTUH)  
MEC black Type I Nut for grill application ONLY.  
(100,000 BTUH)  
MEC red Type 1 NUT approved for RV applications.  
(400,000 BTUH)

## High Flow Hose Features

- 400,000 BTU's
- Excess Flow Safety Shut-Off
- RVIA and NFPA 1192 Compliant
- Brass Ferrules
- 1/4" ID High Pressure Thermoplastic Hose
- 1/4" Inv. Flare and 1/4" MPT connection offered
- 100% Leak Tested
- 350 PSIG Working Pressure

### High Flow Pigtails

Part No.	Approximate Length "X" *	Connection	Connection	Available Packaged**
MER425H-"X"	12, 15, 18, 24	Female QCC, Type I Connection	1/4" Male Inverted Flare	Yes
MER426H-"X"	15, 20	Female QCC, Type I Connection	1/4" MNPT	Yes

\* Replace "X" with the desired hose length i.e. MER425H-15  
 \*\* Packaged option consists of a plastic clamshell with barcode: MER425H-15P



For Your Local Marshall Excelsior Distributor Call 269-789-6700,  
 Fax 269-781-8340 or E-mail: sales@marshallexcelsior.com  
 www.marshallexcelsior.com

